


	<b>Standard Whisper</b>	<b>Compact Whisper</b>	<b>Whisper Elite</b>	<b>Mini Whisper</b>	<b>Mini Green</b>	<b>Whisper Tube</b>
						
<b>Dimensions</b>	86×40×36 mm	70×40×45 mm	125×70×34 mm	55×20×40 mm	50×20×20 mm	65(L)×25(φ) mm
<b>Power Stability</b>	<+/-1% over 15-45°	<+/-1% over 15-45°	<+/-1% over 15-45°	<+/-2% over 15-45°	<+/-2% over 15-45°	<+/-2% over 15-45°
<b>M<sup>2</sup></b>	<1.2	<1.2	<1.1	<1.3	<1.1	<1.3
<b>Beam Shape</b>	Elliptical/Circular	Elliptical/Circular	Elliptical/Circular	Elliptical	Circular	Elliptical
<b>Pointing Stability</b>	< 5 urad/°C	< 5 urad/°C	< 5 urad/°C	< 10 urad/°C	< 10 urad/°C	< 5 urad/°C
<b>Polarization</b>	> 100:1	> 100:1	> 100:1	> 50:1	> 100:1	> 50:1
<b>RMS Noise (20 Hz – 20 MHz)</b>	< 0.2%	< 0.2%	< 0.2%	< 0.2%	< 0.2%	< 0.2%
<b>Wavelength Range</b>	375 – 1064nm	375 – 1064nm	405 – 1500nm	375 – 1064nm	532 nm	405 – 1064nm
<b>Warmup Time (From Cold Start)</b>	<1min	<1min	<1min	<1min	<1min	<2min
<b>ISO, CE, RoHS Compliance</b>	✓	✓	✓	✓	✓	✓
<b>CDRH Certification</b>	✓	✓	✓	Optional	Optional	Optional
<b>USB, RS-232, or Analog Control</b>	✓	✓	✓	Optional	Optional	Optional
<b>Optical Fiber Output Option</b>	✓	✓	✓	Optional	Optional	Optional